



## *Technical Data Sheet*

### **ILUC 6-8"**

*Pneumatic Internal Line-Up Clamp w. Copper Shoes*



(sample picture)

*Technical specifications may be subject to revision without prior notice.  
Subject to print errors. Our General Terms & Conditions apply. Available upon request.*



## SPECIFICATIONS

|                         |           |               |
|-------------------------|-----------|---------------|
| Diameter                | 6-7       | (inch)        |
| ID Range min max        | 128-175   | (mm)          |
| Dimension (approx.)     | 6" x 2500 | (mm)          |
| Weight (approx.)        | 110       | (Kg)          |
| Air Tank 1              | 1         | (liters)      |
| Pressure                | 15        | (bar)         |
| Piston Power (out – in) | 742-710   | (kg @ 10 bar) |
| Pistons                 | 6+6       | (no)          |
| Copper shoes mounted    | 6         |               |
| Motor                   | without   | (hp)          |

ILUC comes configured for one specific ID size at delivery.

Acceptable wall thicknesses 19,1 // 18,3 // 15,9 // 14,3 // 12,7 // 5mm

Kit for other sizes quoted separately.

## FEATURES

- Front Sliding Wheels: 4x
- Rear Sliding Wheels: 4x
- Copper Shoes
- Reach rod Standard 20m (to be assembled/welded onsite)
- Electrical Umbilical 30m, Air Hose 30m & Control Console 24VDC